

Congratulations on your purchase of a premium commercial tapware product from 3monkeez.
Our products have been tested and are manufactured to AS 3718.

SCOPE OF APPLICATION

T-3M2949-2913AB

IMPORTANT INFORMATION



Note: Please follow the below procedures. If the below procedures are not followed it may impact the life of some components and void warranties.

- Pre rinse trigger valve must be installed by a qualified plumber in accordance with the Plumbing Code of Australia (PCA), AS/NZS3500 and the Manufacturer's instructions
- All pipework must be thoroughly flushed to remove any debris prior to installation as foreign materials may cause damage to internal parts and affect performance.

INSTALLATION INSTRUCTIONS

Step 1

Unpack the pre rinse trigger valve, make sure no damage is present.

Step 2

Apply appropriate sealant to joint. Install trigger valve ensuring it is tight.

Step 3

Turn on water supply. Check for any leaks and check functionality of pre rinse trigger valve.

TECHNICAL INFORMATION

Inlet Connections	1/2" MI BSP
Working Pressure Range	150kPa - 500kPa
Flow Rate	3.5LPM
Maximum Operating Temperature	80 Degrees Celcius



STAINLESS STEEL MAINTENANCE AND CLEANING INSTRUCTIONS

Stainless steel products must be cleaned on a regular basis to maintain the ability to resist corrosion. The surface of stainless steel has a protective layer that creates a protective shield against oxidation; which makes it durable and long lasting. Protecting this layer is important to ensure the longevity of this product.

Cleaning stainless steel products is an easy task when done regularly:

- Clear away all debris from the surface with a microfiber cloth or soft sponge; don't use abrasive materials.
- Once cleared of debris, go over the surface with a food safe stainless steel cleaner, bicarb soda or mild detergent and water. The best chemicals for stainless steel contain alkaline and don't have chloride in them.
- To remove stubborn stains, use a good quality stainless steel cleaner and non abrasive cloth.
- Rinse thoroughly with clean fresh water.
- Towel dry the product with a soft dry absorbent cloth after cleaning and use.
- Once dry, use a food safe stainless steel or metal polish. Follow the grain of the metal to ensure the best results and avoid damage.
- Always keep the product clean and dry when not in use.
- Don't leave anything citric on the product as it can etch the surface over time.
- Don't leave soaps and other cleaners on your stainless steel product overnight or damp sponges/cloths on of the product when not in use.

TIP - Cleaning your stainless steel equipment after each use as above will ensure the product remains in good condition.

CARTON CONTENTS - 1x Pre Rinse Trigger Valve

